

## Glassdoor Bookcase Specifications

P. O. Box 1888 Dickson, TN 37056-1888 (866) 446-8686 www.tennsco.com

Materials: Glassdoor bookcases as well as all Tennsco products are fabricated of high quality, cold rolled carbon steel, free of scale or rust and fully pickled. Exposed edges, corners and surface areas are free of sharp edges. Glass doors are made of tempered safety glass (4 gauge) that provides protection from dust and other contaminants. All workmanship is of the highest quality as measured by the industry.

Finish: All steel components shall be thoroughly cleaned and phosphatized for rust resistance in a five-stage pre-treatment process. A high grade of polyester/epoxy powder paint is to be applied electrostatically with a gloss reading of between 55 and 65. The finish shall have a salt spray rating of 250 hours or more.

Shelves: The 18 ga. shelves are 12 ³/4" deep and flanged on both sides for locking into the end bracket lances, which allow the shelves to be adjustable at 2" intervals. They also have a box formation in the fornt and rear and are capable of supporting 50 lbs. per linear foot.

<u>Bottom:</u> The bottom is made of 22 ga. steel. It is flanged on all sides with a box formation to keep materials 2" off the floor.

Back: The back is made of 22 ga. steel, flanged at the bottom with a channel formation in front.

<u>Sides:</u> The 20 ga. sides are flanged at the top, bottom and rear, with a channel formation in front.

<u>Top:</u> The 20 ga. steel top is flanged in front and back and sleekly rounded on top to blend with any style of office furniture.

<u>Sliding Door:</u> The tempered glass doors glide on a rigid PVC track. The track is impregnated with oil to facilitate easy movement. Finger pulls are bonded to the face of the glass doors.

<u>Locks:</u> Doors are equipped with a plunger lock with adjustable bar to prevent unauthorized access.